



ADHESION PROMOTER

Bonds Paint to Plastic

- Three Products in One!
 - 1) Adhesion Promoter
 - 2) Flex Agent
 - 3) Tie Coat
- Safe for all automotive body panels and most other plastics, including TPO, polypropylene, and SMC
- Can be used effectively on metal, fiberglass, and rubber
- Fills 320 grit scratches
- Does not require sanding when used as a Tie-Coat for jambs and edges
- Meets all Federal, State and Local V.O.C. regulations





ADHESION PROMOTER

Technical Data

BULLDOG® ADHESION PROMOTER	
Appearance	Liquid, Hazy, Light Pink to Light Yellow, Mobile, Dries to a Class A Water-white Finish
Vapor Density	Heavier than Air
Percent Volatile	82.75% by weight
Flash Point	32°F
CPSC Flammability Classification	Flammable
MAX V.O.C.	748 grams/liter (6.23 lb/gal)
MAX Vapor Pressure of the V.O.C.	30.6mm Hg at 20°C
Storage	Store between 32°F and 95°F, in the original container.
Coverage	up to 750 sq. ft. per gallon
Shelf Life	2 years from date of manufacture, in an unopened container
DOT	UN1866, Resin Solution, Flammable, 3, PGII
HAPS	Toluene, Xylene, Ethyl Benzene, Styrene
VOC Category	Specialty Coatings
Density	7.5 lbs/gal
Boiling Range	132°F to 380°F

PREPARING PLASTIC PARTS FOR PAINTING

Step 1

Step 2

Step 3

Ordering Information

PRODUCT	SIZE	PACK	LBS	CUBE FT.	WIDTH	DEPTH	HEIGHT	UPC CODE	PALLET QTY.
PTP0123	PT	12	15	.438	11 ¹ / ₁₆	8 ⁹ / ₁₆	8	03019212310-2	90 CASES
QTP0123	QT	6	14	.406	10 ⁹ / ₁₆	7 ¹ / ₈	9 ⁵ / ₁₆	03019212315-7	88 CASES
GTP0123	GL	4	36	.762	13 ¹³ / ₁₆	8 ¹³ / ₁₆	10 ¹³ / ₁₆	03019212325-6	52 CASES



Carefully read all cautions and instructions on product label before use.
For more information about other Klean-Strip products, call or write Klean-Strip Marketing department.

www.kleanstripauto.com

©2007 W.M. Barr & Co., Inc. PO Box 1879, Memphis, TN 38101 Phone: (800) 238-2672 Fax: (800) 621-9508