



# ADHESION PROMOTER

## Bonds Paint to Plastic

- Convenient aerosol application
- Safe for all automotive body panels and most other plastics, including TPO, polypropylene, and SMC
- Can be used effectively on metal, fiberglass, and rubber
- Fills 320 grit scratches
- Does not require sanding when used for jambs and edges
- Meets all Federal, State, and Local V.O.C. Regulations





# ADHESION PROMOTER

## Technical Data

### BULLDOG® ADHESION PROMOTER - ETPO123

Appearance	Dries to a Class A Water-White Finish
Vapor Density	Heavier than Air
Percent Volatile	90.4% by weight
Flash Point of Concentrate	42°F
CPSC Flammability Classification	Flammable
MAX V.O.C.	MIR 2.23 gram ozone/gram
MAX Vapor Pressure of the V.O.C.	N/A
Storage	Replace overcap on container after each use. Contents under pressure. Do not puncture, incinerate or store above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting.
Coverage	up to 100 sq. ft. per can, at 1 mil wet
Shelf Life	2 years from date of manufacture, in an unopened container
DOT	UN1950, Aerosols, flammable 2.1, Limited Quantity Level 3 Aerosol
HAPS	Toluene, Xylene, Ethyl Benzene, Styrene
VOC Category	Aerosol Specialty Coatings

## PREPARING PLASTIC PARTS FOR PAINTING



Step 1

Step 2

Step 3

## Ordering Information

PRODUCT	SIZE	PACK	LBS	CUBE FT.	WIDTH	DEPTH	HEIGHT	UPC CODE	PALLET QTY.
ETPO123	12 oz.	4	5	.152	5 <sup>11</sup> / <sub>16</sub>	5 <sup>11</sup> / <sub>16</sub>	8 <sup>3</sup> / <sub>4</sub>	03019212399-7	168 CASES



Carefully read all cautions and instructions on product label before use.  
For more information about other Klean-Strip products, call or write Klean-Strip Marketing department.

[www.kleanstripauto.com](http://www.kleanstripauto.com)

©2007 W.M. Barr & Co., Inc. PO Box 1879, Memphis, TN 38101 Phone: (800) 238-2672 Fax: (800) 621-9508